

**CANTER**

# FG4X4

DELIVERING  
lower cost-of-ownership.



MITSUBISHI FUSO TRUCK OF AMERICA, INC.

## SPECIFICATIONS

A boost for your business and your bottom line. The Canter® FG4X4 will change the way you think about moving your company forward. Its cost-of-ownership is so low you can measure it by the mile. Well equipped for off-road, it has 9" of ground clearance, locking hubs, heavy-duty axles, all-terrain tires, transfer case and more. Plus a fuel injected diesel engine and automated manual transmission that set new benchmarks for efficiency. All backed by our industry-best 5-Year/175,000-Mile powertrain limited warranty. The Canter FG4X4. It's just the boost your business needs.



Weight ratings	GVWR	14,050 lb.
	GAWR (Front/Rear)	5,730 lb./9,480 lb.
Curb weight	Base model	6,150 lb. (est.)
Body/Payload	Estimated max.	7,900 lb. (see dealer for details)
Dimensions	Wheelbases available	134.4"
	Overall length (cab/chassis)	227.8"
	Usable cab to rear axle	104.8"
	Body sizes accommodated	12' to 15'
Engine	Model	4P10(T5)
	Type	DOHC, 4-cylinder, 4-stroke cycle, water-cooled, turbocharged, intercooled diesel with 4 valves per cylinder
	Displacement	183 cu. in (3.0 L)
	Max. output (SAE, gross)	161 hp @ 3500 rpm
	Max. torque (SAE, gross)	295 lb.-ft. @ 1600 rpm
Air cleaner	Type	Dry paper element with snorkel
Transmission	Standard	Mitsubishi Fuso DUONIC 6-speed OD AMT
Axles	Front	6,175 lb.
	Rear	9,480 lb.
Final reduction gear	Type	Single-reduction hypoid
	Ratio (Std/Opt'l)	5.285/5.714
Top speed, est.	Std diff/Opt'l diff	80/76
Turning diameter	Shortest wheelbase	44.2'
Tires (premium)	Configuration	Single front, dual rear
	Size/Type	235/85R16 10PR LR:E, traction, all positions
Wheels	Size/Configuration	16" x 6"/6-lug
Steering	Type	Ball-nut type with integral-type hydraulic power boost
	Adjustments	Tilt/telescoping steering column with steering lock
Suspension	Front	Laminated leaf springs with shock absorbers
	Rear	Laminated leaf springs with shock absorbers
Brakes	Service	Drum, vacuum/hydraulic-type with ABS
	Parking	Drum/driveline, internal expanding shoe
	Exhaust	Electrically actuated
Frame	Type	Ladder/drop/tapered
	Section modulus	8.15 cu. in. per rail
	Yield strength	44,100 psi
	RBM per rail	359,415 lb.-in.
	Height/width	29.7"/29.6"
Fuel tank	Capacity/location	33 gal./left side
DEF tank	Capacity/location	3.2 gal./right side
Battery	Type/capacity	12-volt, maintenance-free/750 CCA
Electrical	Starter/Alternator	12-volt/12-volt, 140A output
Starting	Cold weather provision	Individual ceramic-tipped glow plugs
Convenience	Windows/door locks	Power operated, one-touch up and down driver's-side window
	Cruise control	Standard (programmable)
	Entry	Keyless, with engine immobilizer standard

## SAFETY

Crush bar in each door, energy-absorbing steering column, daytime running lights, drum brakes with ABS (all wheels), covered open-grate entry steps, forward swing doors for safer entry/exit, high visibility halogen headlamps

## CAB COLORS

ARCADIA SILVER

NATURAL WHITE

JUPITER GREEN

MARS RED

SHANNON BLUE

All models are available immediately in white. Other colors shown may be special ordered at no extra charge.

## FABRIC STYLE

BLUE CLOTH

Vehicle specifications are subject to change without notice. Photos and descriptions included in this spec sheet may vary in comparison to actual vehicle models. For warranty limitations and details, see your local dealer.

PRINTED IN THE U.S.A. 2/11.  
©2011 MITSUBISHI FUSO TRUCK OF AMERICA, Inc.

**Mitsubishi Fuso Truck of America, Inc.**

2015 Center Square Road  
Logan Township, NJ 08085

[mitfuso.com](http://mitfuso.com)

